

LCGTier2/PhaseC Web Preferences

The following settings are ***web preferences*** of the LCGTier2.PhaseC web. These preferences overwrite the ***site-level preferences*** in TWikiPreferences, and can be overwritten by ***user preferences*** (your personal topic, i.e. TWikiGuest in the TWiki.Main web)

Preferences:

- List of topics of the TWiki.LCGTier2/PhaseC web:
 - ◆ Set WEBTOPICLIST = Changes | Index | Search | Go
- Web specific background color: (Pick a lighter one of the StandardColors)
 - ◆ Set WEBBGCOLOR = #D0D0D0
- List this web in the SiteMap:
 - ◆ If yes, set SITEMAPLIST to on, do not set NOSEARCHALL, and add the "what" and "use to..." description for the site map. Make sure to list only links that include the name of the web, e.g. LCGTier2/PhaseC.Topic links.
 - ◆ Set SITEMAPLIST = on
 - ◆ Set SITEMAPWHAT = Describe what this web does.
 - ◆ Set SITEMAPUSETO = ...to do something.
- Exclude web from a web="all" search: (Set to on for hidden webs)
 - ◆ Set NOSEARCHALL =
- Default template for new topics and form(s) for this web:
 - ◆ WebTopicEditTemplate: Default template for new topics in this web. (Site-level is used if topic does not exist)
 - ◆ TWiki.WebTopicEditTemplate: Site-level default template
 - ◆ TWikiForms: How to enable form(s)
 - ◆ Set WEBFORMS =
- Users or groups who ***are not / are*** allowed to ***view / change / rename*** topics in the LCGTier2/PhaseC web: (See TWikiAccessControl)
 - ◆ Set DENYWEBVIEW =
 - ◆ Set ALLOWWEBVIEW =
 - ◆ Set DENYWEBCHANGE =
 - ◆ Set ALLOWWEBCHANGE =
 - ◆ Set DENYWEBRENAME =
 - ◆ Set ALLOWWEBRENAME =
- Users or groups allowed to change or rename this WebPreferences topic: (I.e. TWikiAdminGroup)
 - ◆ Set ALLOWTOPICCHANGE =
 - ◆ Set ALLOWTOPICRENAME = TWikiAdminGroup
- Web preferences that are ***not*** allowed to be overridden by user preferences:
 - ◆ Set FINALPREFERENCES = NOSEARCHALL, ATTACHFILESIZELIMIT, WIKIWEBMASTER, WEBCOPYRIGHT, WEBTOPICLIST, DENYWEBVIEW, ALLOWWEBVIEW, DENYWEBCHANGE, ALLOWWEBCHANGE, DENYWEBRENAME, ALLOWWEBRENAME

Notes:

- A preference is defined as:

6 spaces * Set NAME = value

Example:

◆ Set WEBBCOLOR = #FFFFC0

- Preferences are used as TWikiVariables by enclosing the name in percent signs. Example:

◆ When you write variable %WEBBCOLOR%, it gets expanded to #0099FF .

- The sequential order of the preference settings is significant. Define preferences that use other preferences first, i.e. set WEBCOPYRIGHT before WIKIWEBMASTER since %WEBCOPYRIGHT% uses the %WIKIWEBMASTER% variable.
- You can introduce new preferences variables and use them in your topics and templates. There is no need to change the TWiki engine (Perl scripts).

Related Topics:

- TWikiPreferences has site-level preferences.
- TWikiUsers has a list of user topics. User topics can have optional user preferences.
- TWikiVariables has a list of common %VARIABLES%.
- TWikiAccessControl explains how to restrict access by users or groups.

This topic: LCGTier2/PhaseC > WebPreferences

Topic revision: r7 - 2003-12-26 - PeterThoeny



Copyright © 2008-2024 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback